

**HEI-MEX**

Urethane paint that can be painted  
and peeled off



HEISEN GROUP  
Since 1920

## Peelable Hei-Mex 6600

Hei-Mex 6600 is suitable to prevent tack of urethane gel. It combines elongation and strength enough to follow to the gel even with a thin film. Because of its water-based paint, paint scattering by spray application does less damage to affect the human body and working environment.



Apply this peelable paint on a  
silicone mold

Pour the gel material into  
the mold and demold the cured  
material

The casting product with the  
In-Mold coating is obtained

Character	Milky white liquid
Appearance of coating film	Transparent
Viscosity	20 sec (Anest Iwata viscosimeter NK-2)
Solid content	46 %
Tensile strength	5 MPa
Elongation at break	850 %



【Sales company】  
Heisen Yoko CO., LTD.

【Tokyo Head Office】 Yanagibashi First Building 2-19-6 Yanagibashi Taito-ku Tokyo 111-0052 Japan  
TEL +81-(0)3-3865-3621 FAX +81-(0)3-3865-3638

【Kansai Office】 KS Osaka Edobori Building 1-25-13 Edobori Nishi-ku Osaka 550-0002 Japan  
TEL +81-(0)6-6447-1250 FAX +81-(0)6-6447-1444

【Nagoya Office】 Shirakawa No. 6 Building 2-18-5 Nishiki Naka-ku Nagoya 460-0003 Japan  
TEL +81-(0)52-203-1637 FAX +81-(0)52-203-1639

【Kyushu Office】 Well Tobata Building 1-6 Shioi-machi Tobata-ku Kitakyushu Fukuoka 804-0067 Japan  
TEL +81-(0)93-883-5548 FAX +81-(0)93-883-3566

【Manufacturing company】  
H&K Co., Ltd. <https://handk-heisengp.co.jp/english/index.html>